

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 August 2003 (28.08.2003)

PCT

(10) International Publication Number
WO 2003/071616 A3

(51) International Patent Classification⁷: **H01M 10/50**

1255 10th Street Northwest, Apartment 302, New
Brighton, MN 55112 (US).

(21) International Application Number:
PCT/US2002/040971

(74) Agents: **WEISS, Lucy C.**, et al.; Office of Intellectual
Property Counsel, Post Office Box 33427, Saint Paul, MN
55133-3427 (US).

(22) International Filing Date:
19 December 2002 (19.12.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/357,874 19 February 2002 (19.02.2002) US

(71) Applicant (for all designated States except US): **3M IN-
NOVATIVE PROPERTIES COMPANY** [US/US]; 3M
Center, Post Office Box 33427, Saint Paul, MN 55133-
3427 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **NG, Chin-Yee**
[MY/US]; 1255 Ferndale Street North, Unit 17, Maple-
wood, MN 55119 (US). **GULLICKS, Scott D.**, [US/US];


(81) Designated States (national): AE, AG, AL, AM, AT (util-
ity model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,
CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (util-
ity model), DE, DK (utility model), DK, DM, DZ, EC, EE
(utility model), EE, ES, FI (utility model), FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ,
LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: TEMPERATURE CONTROL APPARATUS AND METHOD FOR HIGH ENERGY ELECTROCHEMICAL CELLS

(57) Abstract: An apparatus and method provides cooling for electrochemical cells of an energy storage device. A number of electrochemical cells are arranged in a spaced apart relationship, each having opposing first and second planar surfaces and being subject to volumetric changes during charge and discharge cycling. A cooling bladder provides temperature control for the energy storage device. The cooling bladder is formed of a conformable thermally conducting material and includes inlet and outlet ports. The cooling bladder conforms to maintain contact with at least the first planar surface or the second planar surface of each cell during volumetric changes of the cells. A heat transfer medium passes between the inlet and outlet ports of the cooling bladder to control an operating temperature of the cells. The cooling bladder can be pressurized to maintain the cells of the energy storage device in a state of compression during charge and discharge cycling.



WO 2003/071616 A3